

MATERIAL SAFETY DATA SHEET
Booster Fluid BFL-A (#15077) for SPIRFLAME®

SECTION 1 -

MSDS Name:
Catalog Numbers:
Synonyms:
Company Identification:
For information,
Emergency Number:

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Acetone
BFL-A or SFV/BFL-A Acetone is the major content in the Booster fluid BFL-A
Dimethylketone; 2-propanone; dimethylketal
SAT address as on headline
PHONE: 866-977-4744 FAX: 413 788 0490
1-800-535-5053 (infotrac)

SECTION 2 -

COMPOSITION, INFORMATION ON INGREDIENTS

CAS#	Chemical Name	%	EINECS#	Hazardous
67-64-1	Acetone	≤ 95	200-662-2	Yes
Proprietary	Additives, various	< 3	proprietary	No
7732-18-5	Water	Balance	231-791-2	No

SECTION 3 -
EMERGENCY OVERVIEW

HAZARDS IDENTIFICATION
DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM.

SAF-T-Data (tm) Ratings (Provided here for your convenience)

Health Rating 2 - Moderate
Flammability Rating 3 - Severe (Flammable)
Reactivity Rating 0 -None
Contact Rating 3 - Severe
Lab Protective Equip GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES;
Storage Color Code CLASS B EXTINGUISHER
Potential Health Effects Red (Flammable)

Inhalation Inhalation of vapors irritates the respiratory tract. May cause coughing, dizziness, dullness, and headache. Higher concentrations can produce central nervous system depression, narcosis, and unconsciousness.
Ingestion Swallowing small amounts is not likely to produce harmful effects. Ingestion of larger amounts may produce abdominal pain, nausea and vomiting. Aspiration into lungs can produce severe lung damage and is a medical emergency. Other symptoms are expected to parallel inhalation.
Skin Contact Irritating due to defatting action on skin. Causes redness, pain, drying and cracking of the skin.
Eye Contact Vapors are irritating to the eyes. Splashes may cause severe irritation, with stinging, tearing, redness and pain.
Chronic Exposure Prolonged or repeated skin contact may produce severe irritation or dermatitis.
Aggravation of Pre-existing Conditions Use of alcoholic beverages enhances toxic effects. Exposure may increase the toxic potential of chlorinated hydrocarbons, such as chloroform, trichloroethane.

SECTION 4 -

FIRST AID MEASURES

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion Aspiration hazard. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a physician immediately.
Skin Contact Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye Contact Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention.

SECTION 5 -

FIRE FIGHTING MEASURES

Fire
Flash point -20C (-4F) CC
Autoignition temperature 465C (869F)
Flammable limits in air % by volume lel: 2.5; uel: 12.8

Extremely Flammable Liquid and Vapor! Vapor may cause flash fire.

Explosion Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back. Contact with strong oxidizers may cause fire. Sealed containers may rupture when heated. This material may produce a floating fire hazard. Sensitive to static discharge.

Fire Extinguishing Media Dry chemical, alcohol foam or carbon dioxide. Water may be ineffective. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

Special Information In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

SECTION 6 -

ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

SECTION 7 -

HANDLING and STORAGE

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

SECTION 8 -

EXPOSURE CONTROLS, PERSONAL PROTECTION

Airborne Exposure Limits (Acetone)

-OSHA Permissible Exposure Limit (PEL): 1000 ppm (TWA)
-ACGIH Threshold Limit Value (TLV): 500 ppm (TWA), 750 ppm (STEL) A4 - not classifiable as a human carcinogen

Ventilation System

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Personal Respirators (NIOSH Approved)

If the exposure limit is exceeded and engineering controls are not feasible, a half-face organic vapor respirator may be worn for up to ten times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece organic vapor respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

SECTION 9 -

PHYSICAL AND CHEMICAL PROPERTIES

Appearance
Odor
Solubility
Specific Gravity
pH
% Volatiles by volume @ 21C (70F)
Boiling Point

Clear, colorless liquid
Fragrant, mint-like
Miscible in all proportions in water
0.79 @ 20C/4C
No information found
100
56.5C (133F) @ 760 mm Hg

Melting Point -95C (-139F)
 Vapor Density 2.0 (Air = 1)
 Vapor Pressure 400 mm Hg @ 39.5C (104F)
 Evaporation Rate ca. 7.7 (BuAc=1)
 Specific Gravity/Density 0.79g/cm3
 Molecular Formula C3H6O
 Molecular Weight 58.14

SECTION 10 -

Stability
 Hazardous Decomposition Products
 Hazardous Polymerization
 Incompatibilities

STABILITY AND REACTIVITY

Stable under ordinary conditions of use and storage.
 Carbon dioxide and carbon monoxide may form when heated to decomposition.
 Will not occur.
 Concentrated nitric and sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, potassium t-butoxide.
 Heat, flames,, ignition sources and incompatibles

Conditions to Avoid

SECTION 11 -

Acetone (67-64-1)

TOXICOLOGICAL INFORMATION

Oral rat LD50: 5800 mg/kg; Inhalation rat LC50: 50,100mg/m3; Irritation eye rabbit, Standard Draize, 20 mg severe; investigated as a tumorigen, mutagen, reproductive effector.
 NTP Carcinogen: Known: No, Anticipated: No
 IARC Category: None

Cancer Lists (Acetone)

SECTION 12 -

Environmental Fate

ECOLOGICAL INFORMATION

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material is expected to quickly evaporate. When released into water, this material is expected to readily biodegrade. When released to water, this material is expected to quickly evaporate. This material has a log octanol-water partition coefficient of less than 3.0. This material is not expected to significantly bioaccumulate. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material may be moderately degraded by photolysis. When released into the air, this material is expected to be readily removed from the atmosphere by wet deposition.
 This material is not expected to be toxic to aquatic life. The LC50/96-hour values for fish are over 100 mg/l.

Environmental Toxicity

SECTION 13 -

DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 -

Domestic (Land, D.O.T.)

Proper Shipping Name
 Hazard Class
 UN/NA
 Packing Group

TRANSPORT INFORMATION

ACETONE
 3
 UN 1090
 II

International (Water, I.M.O.)

Proper Shipping Name
 Hazard Class
 UN/NA
 Packing Group

ACETONE
 3
 UN 1090
 II

SECTION 15

Acetone (67-64-1)
 Chemical Inventory Status -Part 1
 Chemical Inventory Status -Part 1
 Federal, State & International
 Regulations -Part 1
 Federal, State & International
 Regulations -Part 2
 Chemical Weapons Convention

REGULATORY INFORMATION

TSCA: Yes; EC: Yes; Japan: Yes; Australia: Yes
 Korea: Yes, DSL (Canada): Yes; NDSL (Canada): No; Phil.: Yes
 SARA 302: RQ: No; TPQ: No
 SARA 313: List: Yes, Chemical Catg: No
 CERCLA: 5000; RCRA (261.33): U002, TSCA (8(d)): No;
 No

TSCA 12 (b) No
 CDTA Yes
 SARA 311/312 Acute: Yes / Chronic: No / Fire: Yes / Pressure: No
 Australian Hazchem Code 2[Y]E
 Poison Schedule None allocated
 WHMIS This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**SECTION 16 -
 NFPA Ratings**

ADDITIONAL INFORMATIONS



Label Hazard Warning

Health 1
 Flammability 3
 Reactivity 0
 DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM.

Label Precautions

Keep away from heat, sparks and flame.
 Keep container closed.
 Use only with adequate ventilation.
 Wash thoroughly after handling.
 Avoid breathing vapor.

Label First Aid

Avoid contact with eyes, skin and clothing.
 Aspiration hazard. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a physician immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention.

MSDS Creation Date: 12/12/1995
 Revision dates: 12/12/1997
 19/06/2001 04/20/2006
 11/06/2006

The information above is believed to be accurate and represents the best information currently available to us. Spirig has searched various database available to the public, like those of Universities and well known chemical supply houses. However, Spirig makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall Spirig be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Spirig has been advised of the possibility of such damages.